



GLOBAL[®]
VALVES AND FITTINGS CO.
Advance Technology to Control

GLOBAL VALVES AND FITTINGS (INDIA) PRIVATE LIMITED
(AN ISO 9001:2015 Certified Company)

www.globalvalvesfittings.com



UNIT - I



UNIT - II

GLOBAL VALVES & FITTINGS (INDIA) PVT. LTD. is an ISO 9001: 2015 certified company with more than 3 decades of high-quality Specified Product manufacturing experience.

We take immense pride in our products with a dedicated team of professionals in the Design & Development of instrumentation Valves & Fittings under high pressure and temperature environments at the most competitive pricing in the Industry. We are specialized in manufacturing High & Medium Pressure Valves, Needle Valves, Ball Valves, Double Ferrule Fittings, Pipe Fittings, Check Valve / NRV, Valves Manifold, Thermowell, Pressure Regulators & allied accessories.

A total TQM approach: Quality assurance process in place in order to streamline all Procedures & Practices in our operations to achieve extremely high standards of efficiencies. Each manufactured product goes through extreme rigours of stage-wise quality check educing repeat orders from our clients in the field of Oil & Gas Industries, Water Treatment Plants, Pharma Industries, Automation Machineries, Hydraulic Press & Power Packs, Pollution Control Equipments, Marine, Petrochemical and Power Generation application.



TUBE FITTINGS

- Compression type Double ferrule tube fittings
- The Double ferrule optimize sealing and tube gripping function to provide excellent leak-tight connection
- Available in SS304L/SS316L, Monel, Hastelloy, Inconel & Duplex
- Variety of thread type: NPT, BSPT, ISO, SAE
- Sizes: 1/8"~1" pipe thread & 3mm~25mm O.D.
- Material Traceability




PIPE FITTINGS

- Used for process control and instrumentation Connections
- Precision machined from forgings for shaped fittings and from bar stock for straight connectors
- Available in SS304L/SS316L, Monel, Hastelloy, Inconel & Duplex
- Variety of thread type: NPT, BSPT, ISO, SAE
- Male threads are capped for protection
- Sizes: 1/8"~2" pipe.
- Material Traceability









NEEDLE VALVES & GAUGE ROOT VALVES

- Maximum Working Pressure up to 10000 psi (689 bar)
- Working Temperature:
up to 464°F (240°C) with PTFE packing
up to 842°F (450°C) with Graphite packing
- Available in SS304L/SS316L, Monel, Hastelloy, Inconel & Duplex
- Adjustable packing to extend service life.
- Size: 1/4 ~2" pipe thread 3~25mm OD, 1/8"~1" OD
- Leak tight performances testing for every valve with nitrogen/ air at the maximum working pressure
- Panel Mountable(optional)
- Low Operating Torque
- Forged Body Straight & angle pattern.
- 100% factory tested
- Material Traceability



MANIFOLD VALVES

- Maximum Working Pressure up to 10000 psi (414 bar)
- Working Temperature:
-65°F (-54°C) to 464°F (240°C) with PTFE packing
-65°F (-54°C) to 842°F (450°C) with Graphite packing
- Available in SS304L/SS316L, Monel, Hastelloy, Inconel & Duplex
- Available with Pipe to Pipe, Pipe to Flange, Flange to Flange, Remote, Remote Mounting base
- Vent, Direct and Integral Mounting
- Standard Non-rotating trim
- Low Operating Torque
- One piece high strength bar stock and forged body
- 100% factory tested
- Material Traceability




MONOFLANGE VALVES

- Maximum Working Pressure up to 6000 psi (414 bar)
- Working Temperature:
-65°F (-54°C) to 464°F (240°C) with PTFE packing
-65°F (-54°C) to 842°F (450°C) with Graphite packing
- Available in SS304L/SS316L, Monel, Hastelloy, Inconel & Duplex
- Available with Pipe to Pipe, Pipe to Flange, Flange to Flange, Remote, Remote Mounting base
- Vent, Direct and Integral Mounting
- Standard Non-rotating trim
- Low Operating Torque
- One piece high strength bar stock and forged body.
- 100% factory tested
- Material Traceability



CHECK VALVES

- Maximum Working Pressure up to 10000 psi (689 bar)
- Working Temperature:
-10°F (-23°C) to 392°F (200°C) with Viton 'O' ring
- Available in SS304L/SS316L, Monel, Hastelloy, Inconel & Duplex
- Variety of thread type: NPT, BSPT, ISO, SAE
- Size: 1/8 ~2" pipe thread 3~25mm OD, 1/8"~1" OD
- Instant shut off in upstream Condition.
- Compact Design
- 100% factory tested
- Material Traceability



BALL VALVES

- Maximum Working Pressure up to 10000 psi (689 bar)
- Working Temperature:
up to 212°F (100°C) with Delrin packing
up to 464°F (240°C) with PTFE packing
up to 842°F (450°C) with PEEK packing
- Available in SS304L/SS316L, Monel, Hastelloy, Inconel & Duplex
- Size: 1/4 ~2" pipe thread, 3~25mm OD & 1/8"~1" OD
- Leak tight performances testing for every valve with nitrogen/ air at the maximum working pressure
- 100% factory tested
- Panel Mountable(optional)
- Low Operating Torque
- Floating ball design for positive sealing
- Material Traceability
- Compact design
- Single piece design and Three piece design
- 2 Way, 3 Way & 5 Way



RELIEF SAFETY VALVES

- Maximum Working Pressure up to 6000 psi (414 bar)
- Working Temperature from -22°F (-30°C) to 392°F (200°C)
- Available in SS304L/SS316L, Monel, Hastelloy, Inconel & Duplex
- Size: 1/4" ~1" pipe thread
6mm ~25mm OD, 1/4"~1" OD
- Set Pressure from 10 to 6000 psi (3.4 to 414 bar)
- Multiple springs for a wide range of set pressure
- Easy external pressure adjustment
- Label identifies the set pressure range
- 100% factory tested
- Material Traceability



THERMOWELLS

- Available in SS304L/SS316L, Monel, Hastelloy, Inconel & Duplex
- Various range - Threaded, Flanged, Socket weld, Tapered & Straight
- Instrument connection - ½" NPT / NPSM.
- Insertion length (U) up to 28"
- One piece construction
- Other thread sizes available upon request
- Material traceability.



PRESSURE REGULATOR

- Pressure Regulator are available in SS316L
- Available with a variety of porting and material options.
- Piston sensed design in safe and reliable
- Maximum working pressure up to 6000 psi (414 bar)
- Adjustable stop limits maximum outlet pressure
- Low operating torque
- 100% factory tested
- Material traceability
- Back pressure, Single stage & Double Stage.



CONDENSATE POTS

- Available in SS304L/SS316L, Monel, Hastelloy, Inconel & Duplex
- Small thin design & light weight design allows you to combine with other valves in series for safe shutoff.
- End connection NPT, SW as per ANSI B2.1 & B16.11
- Wall thickness schedule 40, 80 & 160
- Maximum working pressure up to 10000 psi (689 bar)
- Size ranging from ½" to 2"
- 100% factory tested
- Material traceability
- 2 Port, 4 Port, 6 Port, 8 Port, 10 Port
- 100% Radiography of pipe joints



AIR HEADER

- Available in SS304L/SS316L, Monel, Hastelloy, Inconel & Duplex
- Variety of end connections -Threaded, Flanged, Socket Weld, will be as per ANSI B16.11
- 100% Radiography of pipe joints.
- Fabrication as per ASME SEC VIII DIV 1 ED
- Material traceability.



PRESSURE GAUGE & ACCESSORIES

- Available in SS304L/SS316L, Monel, Hastelloy, Inconel & Duplex



FORGED FITTINGS

- Available in SS304L/SS316L, Monel, Hastelloy, Inconel & Duplex



TUBES

- Available in SS304L/SS316L, Monel, Hastelloy, Inconel & Duplex



HIGH-PRESSURE VALVES

- Maximum Working Pressure 500 bar
- Available in CS (White Zinc plated)
- Size ranging from 1/4" to 2"
- Connection: BSP, NPT & SW



GLOBAL VALVES AND FITTINGS (INDIA) PRIVATE LIMITED
(AN ISO 9001:2015 Certified Company)



HEAD OFFICE & FACTORY

UNIT I

B/9(A/34), K.J.B. Compound,
Opp. Nahar Amrit Shakti, Khairani Road,
Sakinaka, Mumbai - 400072, India.
Cell: +91-9930939595
E-mail: info@globalvalvesfittings.com

FACTORY

UNIT II

Building No-6, Sec-II A, Renaissance
Industries City, Village - Washere,
Taluka - Bhiwandi, District - Thane,
Maharashtra - 421302
Cell: +91-9821554388
E-mail: info@globalvalvesfittings.com

BRANCH

HYDERABAD

4-2-263 to 265, Shop No. 2, Vonamala Arcade,
Mahankali Street, Ranigunj, Secundarabad,
Hyderabad, Telangana - 500003, India.
Cell: +91-7032880577
E-mail: hyd@globalvalvesfittings.com

DELHI E-mail: delhi@globalvalvesfittings.com

PUNE E-mail: pune@globalvalvesfittings.com

AUTHORISED DISTRIBUTOR

UAE

M/s. GEE-LOK Valves Pipes & Fittings Trading LLC.
Shop No-4, Al Nakheel Road, Deira,
Dubai, UAE.
Tel.: +971-52-4534877
E-Mail: info@geelok.com
Website: www.geelok.com

GERMANY

M/s. Global Valves & Fittings Co. Germany
Bahnhofstraße 31 90559 Burghann Germany
Mobile: +49 170 1237049
Email: j.buchmann@freenet.de

MEXICO

Ssteel Comercializadora Industrial, SA de CV.
Tel. Cd. México (0155) 4751 5923
Nextel ID 42*908628*2
Tel.: (0155) 6355 5962

IMPORTANT NOTICE:

- The product data in this catalogue was obtained under specific test conditions that may vary substantially from actual site conditions and / or customer needs.
- Purchasers or other end users of our products should rely solely on their system design engineers while selecting products for a particular system, and when determining the suitability of any system in which our product is to be installed.
- The company shall bear no liability regarding product selection criteria or decisions, nor shall be liable (including direct, special or consequential damages including, but not limited to, lost profits or income) in regard to any product which has been damaged by misuse, improper handling or accident, or as a result of service or modification by anyone other than an authorized employee or agent of our company, or being subjected to use under conditions, or combinations of conditions, that are not compatible with that particular product.

For Dealership franchises please feel free to contact us.

www.globalvalvesfittings.com